

Recipro Saw LXT®

DJR186

18V • 0 – 2 800 min⁻¹ • 32 mm

Efficient basic reciprocating saw

An efficient reciprocating saw for spark-free cutting of metal and demolition work. Stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Strokes per Minute (SPM)	0 - 2800 min ⁻¹
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	3,5 - 3,8 kg
Product Dimensions (L x W x H):	486 x 81 x 223 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level, Cutting Boards	13,0 m/s ²
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s ²

User benefits

- Compact and lightweight for reduced operator fatigue
- Slim design with rubberised grip for comfort
- Tool-less blade change and shoe adjustment
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.uk.com



Related products

Optional AC

B-10394

Reciprosaw Blade 305 x 1,5 mm



B-44432

Reciprosaw Blade Set 6 pcs



B-44448

Reciprosaw Blade Set 6 pcs



P-04880

Reciprosaw Blade 150 x 1,4 mm



Other

User manual

Parts drawing