

Plunge Cut Saw LXT®

DSP600

18V X2 • 2 500 – 6 300 min⁻¹ • 165 mm

Precise brushless plunge cut circular saw for professional use

A precise plunge cut circular saw with a brushless motor. Two 18V LXT batteries offer a voltage of 36V. This fast saw has an adjustable speed of between 2 500 and 6 300 min⁻¹. Achieves neat cutting results when used with a guide rail.



Technical specifications

Nominal Battery Voltage	2 x 18 V
Voltage LXT	✓
Max. Cutting Depth at 90°	56 mm
Max. Cutting Depth at 45°	40 mm
Max. Bevel Range (Left)	- 1 / 48 °
No load speed	2500 - 6300 min ⁻¹
Sound Power Level (L _{WA})	103 dB(A)
Sound Pressure Level (L _{pA})	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	4,4 - 5,1 kg
Product Dimensions (L x W x H):	346 x 241 x 272 mm
Brushless Motor	✓
Blade Diameter	165 mm

User benefits

- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makitauk.com



Related products

Optional AC

165447-6 Parallel Guide		194367-7 Guide rail, 3 000 mm	
196664-7 Bevel guide set		198885-7 Guide rail joint connector set, 2 pcs	
199140-0 Guide rail, 1 000 mm		199826-6 Quick-Release Ratcheting Guide Rail	
821552-6 Makpac case (4)		839290-6 MakPac (4) Inlay	

Other

User manual

Parts drawing