

Circular Saw LXT®

DSS611

18 V • 3 700 min- • 165 mm

18V LXT® Cordless saw that cuts at high rotational speed of 3,700 RPM . Saw's grip provides more control and comfort. Easy to adjust cutting depth with safety cover with calibration line. Aluminum base provides high quality and toughness for better work results. Bevel cuts from 0° to 45° for the most common cutting applications



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Max. Cutting Depth at 90°	57 mm
Max. Cutting Depth at 45°	40 mm
Max. Cutting Depth at 50°	36 mm
Max. Bevel Range (Left)	0 - 50 °
No load speed	3700 min ⁻¹
Sound Power Level (L _{WA})	104 dB(A)
Sound Pressure Level (L _{pA})	96 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	2,9 - 3,2 kg
Product Dimensions (L x W x H):	347 x 202 x 228 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Blade Diameter	165 mm

User benefits

- Smooth cutting at high rotational speed of 3,700 RPM
- Ergonomic soft grip handle provides increased comfort
- Safety cover with calibration line for adjusting cutting depth
- Bevel cuts 0°- 45°
- Large bevel lock lever; Easy to operate even if the machine is placed close to the wall, because you do not need to reach for the rear of the machine to turn the lever
- Externally accessible brushes for easy serviceability

Link to product - www.makita.uk.com



Related products

Optional AC

141353-9

Plastic Carrying Case



164095-8

Parallel Guide



783203-8

Hex Wrench 5 Mm



821551-8

Makpac case (3)



837642-5

MakPac (3) Inlay



Other

User manual

Parts drawing